



DASH NO.	L1	L2	W	V
-1	11.4 MAX.	6.00	2.40 lb. MAX.	80 cu. in. MIN.
-2	11.4 MAX.	6.00	2.40 lb. MAX.	80 cu. in. MIN.
-3	8.4 MAX.	3.00	1.80 lb. MAX.	53 cu. in. MIN.
-4	8.4 MAX.	3.00	1.80 lb. MAX.	53 cu. in. MIN.

**ARDE Part Number 4600**

<b>Volume (cubic inches)</b>	<b>53/80</b>	<b>Material of Construction</b>	
<b>Operating Pressure (psig)</b>	<b>600</b>	<b>Tank</b>	<b>Cryoformed CRES 301</b>
<b>Proof Factor</b>	<b>1.5</b>	<b>Porting Interface</b>	<b>CRES 304L</b>
<b>Minimum Burst Factor</b>	<b>4.0</b>		
<b>Actual Rupture Pressure (psig)</b>	<b>2970</b>		
<b>Weight (pounds)</b>	<b>1.8/2.4</b>		
<b>Qualification Basis Standard</b>	<b>MIL-STD 1522A</b>	<b>Environmental Vibration Load</b>	
	<b>AIAA-S-080</b>		<b>Contact ARDE</b>